

# REEVALUATING FLOOD PROTECTION LEVEL OF SERVICE

## FLORIDA STORMWATER ASSOCIATION 2022 ANNUAL CONFERENCE



Akintunde Owosina P.E.  
Chief, Hydrology and Hydraulics Bureau  
South Florida Water Management District



Michael J. DelCharco, P.E., CFM  
Taylor Engineering  
Sr. Vice President of Water Resources



Matahel Ansar Ph.D., P.E.  
Chief, Hydrology and Hydraulics Bureau  
South Florida Water Management District



# FLOOD PROTECTION LEVEL OF SERVICE PROGRAM

A KEY TO FLOOD RESILIENCY IN SOUTH FLORIDA




Akintunde Owosina P.E.  
Chief, Hydrology and Hydraulics Bureau  
South Florida Water Management District



# SFWMD - Who we are and what we do



## SOUTH FLORIDA WATER MANAGEMENT DISTRICT

- Oldest and largest of the state's five regional water management districts
- Protecting water resources in the southern half of the state since 1949
- Our mission: To safeguard and restore South Florida's water resources and ecosystems, protect our communities from **flooding**, and meet the region's water needs while connecting with the public and stakeholders





# FLOOD CONTROL: Central & Southern Florida Project





# Water Management System


- 2,060 miles of canals
- 2,028 miles of levees
- 160 major drainage basins
- 1,413 water control **structures**
- 71 pumping stations
- 60,000 acres of regional wetland Stormwater Treatment Areas
- Lake Okeechobee
  - 450,000 acre water storage area
- Water Conservation Areas
  - 959,000 acre water storage








# Flood Protection Responsibility

- Primary
  - USACE
  - SFWMD
- Secondary
  - Local Governments
  - Special Districts
- Tertiary
  - Home Owners Associations
  - Private Land Owners






# Sea Level Rise Trends in South Florida (NOAA)



- Linear Mean Sea Level Trend
- Upper 95% Confidence Interval
- Lower 95% Confidence Interval
- Monthly mean sea level with the average seasonal cycle removed



# Sea Level Rise Trends in South Florida (NOAA)





# EFFECT OF HIGH TAILWATER CONDITION



Learn more about how sea level rise and other climate change impacts are affecting water resources management and flood protection in South Florida:

<https://vimeo.com/416090381/a11cead328>



# ... The Manager's Question ...


## **We have the aging infrastructure approaching or past design end of life:**

- Do I replace them and if so When do I replace them ?
- What do I replace them with ?
  - In kind - same as it was? or
  - Different to accommodate known changes since design and projected changes?
- Where and how ?
  - What goes first, what happens next?
  - What happens downstream of our current assets?
- What liability or risk am I exposed to – due to action or inaction
- Who pays for the fix ?
- What assurances do I have ? (responsibility to manage public funds) considering high uncertainty



# Flood Protection Response


- **Flood Protection Level of Service program:**
  - Assess flood protection performance of flood control infrastructure
  - Support decision making on prioritizing improvements and adaptation



Lower East Coast  
LOS Basins



C-7 Basin (Miami Dade)




Big Cypress Basin



# Flood Protection Level of Service Program


- Identify and prioritize long-term District infrastructure needs.
- Assess level flood protection throughout the 16-counties of the SFWMD – relative to design
- Identify at-risk structures and needed improvements to operations, canal conveyance or structures
- Provide a formal process to initiate retrofit and adaptation efforts for future infrastructure improvements and/or modification of regulatory criteria
- Incorporate resilient design standards and construction
- Coordinated with SFWMD Operations, local government entities, drainage districts and other agencies with flood control or related responsibility






# Three Phases of the FPLOS Program

- **FPLOS Assessment:**
  - Identify location of potential challenge
  - Identify time horizon of potential challenge
  - Prioritize watersheds for detailed resilience studies
- **FPLOS Resilience Study and Adaptation Design**
  - Based on findings of assessment
  - Detailed study focused on identifying most cost effective adaptation
  - Involves solution search in all three tiers
  - Identification of uncertainties and time horizon for implementation
  - Culminate with preliminary design sufficient for cost development
- **Resilient Infrastructure Implementation**
  - Include the recommendations in SFWMD Flood Resiliency Plan
  - Final design, permitting and construction of sequenced adaptation






# Ongoing and Recently Complete Studies




FLOS for C-1, C-100, C102, and C-103 Watersheds

Completion: May, 2022



C2, C3W, C5 and C6 Watersheds

Completion date: September 2022



C-111, Model Land, and L-31NS Watersheds

Completion date: September 2022

## Completed Assessments



- C4 Basin
- Big Cypress Basin
- C7 Basin
- C8/C9 Basins
- Broward County

## New Starts this year:




- Upper Kissimmee Basin
- Palm Beach County



# Activities Completed in a Typical FPLOS Adaptation and Mitigation Planning and Design

- Plan for future extreme rainfall, SLR and development
- Focus on full system, primary, secondary and tertiary
- Public planning process that integrates input and strategies in all three tiers
- Mitigation and adaptation strategies in all tiers
- Hydraulic and hydrologic model of the strategies
- Damage assessment without adaptation and with each identified strategy or combination of strategies
- Sequencing and combination of courses of action
- Selection of optimal course of action
- Basis of design level evaluation of selected plan





# Activities Completed in a Typical FPLOS Adaptation and Mitigation Planning and Design






# Supporting Decision Making Under Deep Uncertainty

- Infrastructure cost is high, so is the cost of doing nothing
- There is significant uncertainty
- How to make informed decisions that do not preclude other courses of action
- The difference between a good plan and an implemented plan

## Dynamic adaptive policy pathways



Free Book



# Some of our Challenges

- Working in an environment with deep uncertainty
  - Future climate scenarios – including rainfall
  - Rate of sea level rise
  - Appropriate initial groundwater levels or antecedent conditions
  - Storm Surge projection at our coastal structures
  - Compound events (rainfall, storm surge and groundwater levels)
- Project funding
- Facilitating decision making







# TAYLOR ENGINEERING, INC.

## Flood Protection Level of Service Provided by Existing Infrastructure for Current and Future Sea Level Conditions in Nine Broward County Watersheds

Presentation of Major Findings,  
Current and Future Conditions

8/17/2021

Michael J. DelCharco, P.E., CFM  
Taylor Engineering  
Sr. Vice President of Water Resources






# Overview

- Current Conditions Model Development and Calibration
- Future Conditions Design Storms Setup
- FPLOS Assessments of all Nine Watersheds
- Potential Mitigation Strategies



# Nine Watersheds Represented in MIKE SHE and MIKE HYDRO


- Hillsboro
- C-14 West
- C-14 East
- C-14 East
- Pompano
- C-13 West
- C-12 West
- North New River West
- C-11 West
- C-11 East





# Model Calibration and Validation


- Calibrated to “No-name” rainfall event June 5-7, 2017
  - 4 inches in the southeast to 16 inches in the northwest
- Calibration Target:
  - +/- 10% to 20% peak discharge and total discharge volume
  - +/- 0.5 ft headwater/tailwater and groundwater elevation
- NEXRAD 15-minute rainfall data 2 km x 2 km pixel resolution
- Recorded operations used for gates and pumps
- Tidal structure tailwater forced based on observed data
- Validated to Hurricane Irma rainfall event from September 9-11, 2017
  - 6 inches in the east to 10 inches in the west





# Current Conditions Model Setup


- Rule Based Structure Operations
- Gridded NOAA Atlas 14 rainfall Depths
- SFWMD-provided storm surge tidal boundaries
- “Full-bowl” initial surface water conditions
- Peak rainfall and peak surge occur at same time
- 5-year, 10-year, 25-year, and 100-year storm events






# Future Conditions Model Setup

- 13,650 acres identified for land use change.  
Parameters affected:
  - Topography
  - Overland Manning's Roughness
  - Detention Storage
  - Paved Area Runoff Coefficient
- C-9 & C-11 Impoundments represented
- SFWMD-provided storm surge tidal boundaries with 1, 2, and 3 ft SLR on 2019 sea level
- Future conditions initial groundwater elevations, influenced by SLR






# SFWMD-Generated Tidal Boundaries Applied at 7 Tidal Outfalls







# Future Initial Groundwater Elevation Difference Maps



SLR1



SLR2



SLR3



# FPLOS Performance Measures Evaluated


For 5-Year, 10-Year, 25-Year, and 100-Year Design Storms:

- PM #1 – Maximum Stage Profiles for Primary Canals
- PM #2 – Maximum Area-Weighted Discharge, filtered to remove tide
- PM #3 – Structure Performance – Effects of Sea Level Rise
- PM #4 – Maximum Conveyance Capacity at tidal structures (filtered)
- PM #5 – Frequency of Inundation (Flood Inundation Maps)
- PM #6 – Duration of Flooding Maps (Overland) and Duration for Primary Canals to Recede to Reference Elevation




# C-14 East Basin

- 10-yr FPLOS for SLR1 and less than 5-yr FPLOS for SLR2 and SLR3
- 25-Yr SLR1 and 5-Yr SLR2/SLR3 results in several bank exceedances
  - Elevated stages & bank exceedances directly contributes to flooding of urban areas






Cypress Creek (C-14 East Basin) 5-Year Future Conditions Design Storm  
 Maximum Water Surface Profile: 1, 2, and 3 ft Sea Level Rise Scenarios






**Cypress Creek (C-14 East Basin) 10-Year Future Conditions Design Storm  
Maximum Water Surface Profile: 1, 2, and 3 ft Sea Level Rise Scenarios**




**Landmarks along Cypress Creek (C-14 East Basin)**  
Distance from Upstream End of Reach (ft)



Cypress Creek (C-14 East Basin) 25-Year Future Conditions Design Storm  
 Maximum Water Surface Profile: 1, 2, and 3 ft Sea Level Rise Scenarios



Cypress Creek (C-14 East Basin) 100-Year Future Conditions Design Storm  
 Maximum Water Surface Profile: 1, 2, and 3 ft Sea Level Rise Scenarios



Landmarks along Cypress Creek (C-14 East Basin)  
 Distance from Upstream End of Reach (ft)

- C-14 Canal
- S-37B
- N Palm Aire Drive
- W Palm Aire Drive
- FL-845 (Powerline Road)
- Train Tracks Bridge
- W McNab Rd
- North Andrews Ave
- Interstate 95
- S-37A (Tidal Outfall)







# PM #2- Maximum Discharge Capacity through the Primary Canal

- Allowable discharge rate of 69.2 CSM (25-year design frequency) for C-14 (whole basin)
- 25-year CSL discharge rate = 270.1 CSM
  - 7% to 47% increase under future SLR
- CSM increases as sea level rise increases
  - Increased TW and reverse discharge cause increased HW
  - Continuous discharge into Cypress Creek through Structure S-37B
    - Stages stay elevated and do not drop as quick as the tide after storm surge has passed
    - Increased discharge due to head difference across the structure / timing of gate / flow regime

Drainage Basin	Inflow	Outflow	Water Control Catchment Area (sq.mi)	Design Storm	Peak 12-Hour Moving Average Discharge from the Contributing Drainage Area (cfs/sq.mi)			
					CSL	SLR1	SLR2	SLR3
C-14 East	S-37B	S-37A	2.69	5-Year	151.3	161.1	172.1	214.2
				10-Year	192.8	202.9	225.7	279.3
				25-Year	270.1	288.2	338.3	397.1
				100-Year	448.0	527.4	542.9	633.2



# PM #2- Maximum Discharge Capacity through the Primary Canal







# PM #3- Structure Performance

- Design discharge of 3890 cfs exceeded for all but the 5-year SLR scenarios
- S-37A predicted to be sensitive to SLR:
  - Peak 12-hour discharges changing by +/- 0 % to 3%
  - Peak HW increasing by:
    - 4% to 8% (SLR1)
    - 17% to 20% (SLR2)
    - 29% to 35% (SLR3)




# PM #3- Structure Performance

- Peak stages exceed the static HW/TW design assumptions:
  - 3.2 ft design HW
    - Simulated peak 5.7 ft to 9.2 ft
    - 2.5 ft to 6.0 ft violation
  - 2.2 ft design TW
    - Simulated peak 5.2 ft to 9.2 ft
    - 3.0 ft to 7.0 ft violation






## PM #4- Peak Storm Runoff




## PM #4- Peak Storm Runoff









# PM #5- Flood Depth Difference Maps: Future minus Current Conditions



25-Year SLR1




25-Year SLR2



25-Year SLR3

## Flooding Depth Difference (ft)




Note: Flooding Shown Only Over Urban Land Uses







# PM #6- Flood Duration Difference Maps: Future minus Current Conditions



25-Year SLR1




25-Year SLR2



25-Year SLR3

## Flood Duration Difference (hour)



Note: Flooding Shown Only Over Urban Land Uses



# FPLOS Summary- Highest LOS Ratings

- Hillsboro Basin: 100-yr LOS for all scenarios
- C-13 West: 25-yr CSL, 25-yr SLR1, 10-yr SLR2, LT 5-yr LOS for SLR3
- C-12 West: 25-yr CSL, 10-yr SLR1, less than 5-yr SLR2 & SLR3
- North New River West: 100-yr SLR1, 25-yr SLR2, 10-yr SLR3
- C-11 West: 10-year LOS for all scenarios

# FPLOS Summary- Lowest LOS Ratings

- C-11 East: 10-yr CSL, 5-year LOS for all SLR
- Pompano: 5-yr CSL, less than 5-year LOS for all SLR
- C-14 West: 5-yr CSL, 5-year SLR1, less than 5-yr SLR2 & SLR3
- C-14 East: 25-year CSL, 10-year SLR1, less than 5-yr SLR2 & SLR3





# Project Background

- Original flood protection system designed in the 1950's
  - Did not account for today's sea level changes
- Flood Protection Level of Service program (FPLoS) needs tail water data:
  - range of storm frequencies
  - future sea levels
- There are limited gauge data in the region.
- Historical statistics may no longer reflect future conditions.
- Use physically-based computer models to evaluate propagation of storm surge in canals leading up to the structures.



# Technical Background


## What is Storm Surge?

- Elevated ocean surface due to wind and pressure
- Wind stress pushes water
- Wind stress generates waves
- Wave radiation stresses also push on water column

## Factors that influence surge

- Wind speed
- Track angle
- Forward speed
- Radius to maximum wind (size of the storm)

Other factors: bottom slope, landfall location



Saffir-Simpson Hurricane Scale			Central Pressure	Winds (mph)	Surge	Damage
Category	Wind Speed		Millibars			
	mph	knots				
5	≥156	≥135	< 27.0	>155	>18'	Catastrophic
4	131-155	114-134	27.0-27.17	115	13-18'	Extreme
3	111-130	96-113	28.47-27.91	110	9-12'	Extensive
2	96-110	84-95	965-980	96-110	6-8'	Moderate
1	74-95	65-83	≤ 980		4-5'	Minimal
Non-Hurricane Classifications						
Tropical Storm	39-73	34-64				
Tropical Depression	0-38	0-33				


Charley (4) moderate  
 Katrina (3) catastrophic  
 Ike (2) catastrophic



# What about Waves?



- Breaking waves also contribute to the total water level through wave runup/setup







# Two Scales of Models Coupling

- **Regional Scale**

- ADCIRC--2D shallow-water equations based
- SWAN--spectral wave model
- **Coupled ADCIRC & SWAN**
- Covers the western Atlantic Ocean and Gulf of Mexico
- Includes Biscayne Bay
- Some nearshore overland regions




- **Local Scale**

- DFLOW (Delft3D) FM hydrodynamic model
- SWAN
- **Coupled DFLOW FM & SWAN**
- Highly refined in Biscayne Bay
- Includes extensive overland areas
- SFWMD canal network



# Local Scale Modeling

- D-Flow FM + SWAN (waves set up)
- Unstructured mesh with 1.8 M elements and 940K nodes
- Solves shallow water equations in 2D and 3D
- Adaptive time step
- Resolution 3 m (inland) to 0.5 km (offshore)
- 3D simulation with 7 vertical sigma layers
- Dynamic control of gate structures
- Uses ADCIRC+SWAN results as boundary condition




Zoom in






# Model Topo and Friction

Topography



Mesh edges follow critical geometries



Bottom Friction



Frictional resistance and dry cells added at bridge crossings



# Hurricane-induced wave height along Miami River
















# Model Application -- Hurricane Irma (2017)



■ Tropical depression ( $\leq 38$  mph) ■ Tropical storm (39–73 mph) ■ Category 1 (74–95 mph) ■ Category 2 (96–110 mph) ■ Category 3 (111–129 mph) ■ Category 4 (130–156 mph) ■ Category 5 ( $\geq 157$  mph)

The track of Hurricane Irma (2017). (Source: [https://en.wikipedia.org/wiki/Hurricane\\_Irma#/media/File:Irma\\_2017\\_track.png](https://en.wikipedia.org/wiki/Hurricane_Irma#/media/File:Irma_2017_track.png))


# Irma (2017)



Comparisons of tailwater level (m) at ten gates (ocean side) during Hurricane Irma (2017).



# Model Application -- Sea level rise scenarios (1ft, 2ft & 3ft)




# Summary

- Biscayne Bay Storm Surge Model has been calibrated and validated.
- The model has successfully been applied to Irma (2017) and Bertha (2020) hindcast storm surge studies for FPLOS project
- The model is ready for use to examine individual regions in more detail or to look at wider range of return periods as well as land use planning and to support other resiliency projects
- This model can further be extended to other regions such as coastal Broward county, and also to dynamically simulate gate operations and resulting flows.



# QUESTIONS ?



# Questions?

