# UNIVERSITY of FLORIDA

### Background

Water pollution, especially harmful algal blooms (HABs), caused by excessive input of nutrients is a serious problem worldwide. Nitrogen (N) compounds, such as nitrate (NO3<sup>-</sup>) ions, are the most widespread water contaminants. Florida is famous for its large and diverse agricultural industry,

which could discharge nitrate by stormwater into the environment unintentionally after storms. Meanwhile, as Florida population increases, the construction of living buildings has changed the natural landscapes into communities with impervious surfaces, causing more and more nitrate-containing unmanaged urban stormwater. An elevated NO3<sup>-</sup> concentration can compromise water ecosystems, posing risks to both aquatic life and human health. Therefore, further treatment of these NO3<sup>-</sup> containing stormwater is required.

#### **Constructed Wetland**

Constructed wetlands (CWs) has been proven as an effective technique for treating wastewater, which is also used widely around the world due to their simple operation, low cost, and low energy consumption. With the restricted oxygen transportation as a prominent



characteristic, horizontal subsurface flow constructed wetlands (HSCWs) present a promising approach to further reduce the levels of nitrogenous compounds, particularly of NO3<sup>-</sup>-N, in wastewater discharges.



## Fe-modified Biochar Enhances Microbial Nitrogen Removal Capability of Constructed Wetland

### <u>Yicheng Yang<sup>1</sup></u>, Wen Jia<sup>2</sup>, Yulin Zheng<sup>1</sup>, Jinsheng Huang<sup>1</sup>, Yue Zhang<sup>1</sup>, Bin Gao<sup>1,\*</sup>

1. Department of Agricultural and Biological Engineering, University of Florida, Gainesville, Florida, USA 2. State Key Laboratory of Pollution Control and Resource Reuse, School of the Environment, Nanjing University, Nanjing, China



### Microorganisms & N Cycles

Microorganisms are the driving pump for N transformation and removal inside the CWs. The microbial processes include N fixation, mineralization, nitrification, denitrification, anaerobic ammonium oxidation (anammox), dissimilatory nitrate reduction, among others. Only **denitrification** and **anammox** are considered as permanent N removal pathways. Denitrifying bacteria constitute a large physiological group. Nitrite reductase genes (nirS and nirK) and nitrous oxide

reductase gene (nosZ) are used as functional markers to investigate the denitrification process. The information about the anammox bacteria in CWs is rather limited, although CWs are assumed to offer favorable conditions for anammox.



### **Fe-Modified Biochar**

**Biochar** is a carbon-rich solid produced upon pyrolysis of organic plant and animal materials at high-temperature in a low- or no-oxygen environment. It can remove pollutants due to several unique properties.

**Fe** in different valence and chemical forms, such as zero-valent iron,  $Fe^{2+}/Fe^{3+}$ , iron oxides, can facilitate the nitrification, denitrification and anammox for N removal from wastewater.

**Biochar:** 

- High specific surface area
- Micropore volume
- Nutrient retention
- Provision of labile carbon
- Activated by HCI, electrostatic adsorption of anion, such as NO3<sup>-</sup>-N
- Carbon as electron donor

**Fe-modified biochar (FeB)** has a substantial potential to improve the performance of CWs on N removal.





- Reactive element for N cycles
- Facilitate the denitrification
- Facilitate the anammox
- Iron (hydr)oxides affinity toward oxy-anion ions, such as NO3<sup>-</sup>-N







Florida Stormwater Association